



Universal PCI Serial Boards

The perfect solution for adding multiple high-speed serial ports to any PC, Server, Thin Client or Embedded System



Quatech Low Profile PCI boards provide truly universal connectivity, enabling a single product to be used to implement systems with dramatically different resource requirements. This makes Quatech boards the most robust, most flexible, and most economical choice for any application requiring multiple serial ports.

Quatech boards use a universal PCI connector compatible with both the 3.3V connector key required by the PCI 2.3 and later specification and the 5V connection used by older systems. They are designed on the smallest MD1 Low Profile footprint, but come with both a full size ORB for standard systems, and a smaller ORB for use in Low Profile backplanes to fit even 2U racks without riser cards. In addition, our wide range of OS options facilitates both system upgrades and multiplatform installations.

- One, two or four independent serial ports
- RS-232 or RS-422/485 boards
- Auto enable/disable RS-422/485 transmitter
- Universal PCI connector, 3.3V and 5V
- MD1 Low Profile PCI board (fits 2U racks)
- Speeds up to 921.6 kbps
- 16550 UARTs with 16-byte FIFOs (1,2,4 port)
- 16750 UARTs with 64-byte FIFOs (8 port)
- All ports share a single PCI interrupt
- Win. 95/98/Me/NT/2000/XP/Vista, LINUX, DOS
- Five year warranty
- RoHS compatible



www.quatech.com

RS-232 Board Specifications

Bus Interface: 32-bit, 33 MHz PCI Bus specification 2.3 compliant

OS Support: Windows 95/98/Me/NT/2000/XP/Vista, Linux, OS/2, DOS

Data Rate: 921.6 kbps (max)

Serial Ports: **SSCLP:** 1 **DSCLP:** 2 **QSCLP:** 4 **ESCLP:** 8

UARTs: **S/D/QSCLP:** 16550 UARTs; 16-byte FIFOs (1 per port)
ESCLP: 16750 UARTs; 64-byte FIFOs (1 per port)

Transceiver: ICL3245CA or compatible

Drivers:

High Level Output: +5V (min), +5.4V (typ)

Low Level Output: -5V (min), -5.4V (typ)

Transition Time (THL-TLH): 25ns (typ)

Receive Buffers:

Voltage Range: -25V (max), -25V(min)

Transition Time (THL-TLH): 50ns (typ)

Environment:

Operating: 0°C to 70°C

Storage: -50°C to 80°C

Humidity: 10% to 90%

Power Requirements: +5V, 260mA (typ)

Size:

MD1 Board: 63.55mmH x 119.91mmW (fits 2U racks)

Low Profile PCI Bracket: 79.20mm H
(Standard PCI bracket also included)

Connectors:

SSCLP: DB-9 male

DSCLP: DB-25 male to cable with 2 DB-9 male

QSCLP: HD-44 female to cable with 4 DB-9 male

ESCLP: VHDCI-68 male to cable with 8 DB-9 male

Certifications: CE, FCC Class B, RoHS and WEEE compliant

Ordering Information:

SSCLP-100: One port RS-232 board

DSCLP-100: Two port RS-232 board with cable

QSCLP-100: Four port RS-232 board with cable

ESCLP-100: Eight port RS-232 board with cable

RS-422/485 Board Specifications

Bus Interface: 32-bit, 33 MHz PCI Bus specification 2.3 compliant

OS Support: Windows 95/98/Me/NT/2000/XP/Vista, Linux, OS/2, DOS

Data Rate: 921.6 kbps

Serial Ports Provided: **SSCLP:** 1 **DSCLP:** 2 **QSCLP:** 4
(each configurable as RS-422 or RS-485 for full or half duplex)

UARTs: **SSCLP/DSCLP:** 16550 UARTs; 64-byte FIFOs (1 per port)
QSCLP: 16750 UARTs; 64-byte FIFOs (1 per port)

Transceiver: MAX3076E or compatible

Drivers:

Differential Voltage: $\pm 3.3V$

Transition Time (TLH): 52ns (typ)

Transition Time (THL): 60ns (typ)

Receive Buffers:

Differential Input Threshold: $\pm 0.2V$

Voltage Range: -7V to +12V Common Mode Input

Transition Time (THL-TLH): 65ns (typ)

Environment:

Operating: 0°C to 70°C

Storage: -50°C to 80°C

Humidity: 10% to 90%

Power Requirements: +5V, 260mA (typ)

Size:

MD1 Board: 4.725" x 2.5" (fits 2U racks)

Low Profile PCI Bracket: 3.118" H
(Standard PCI bracket also included)

Connectors:

SSCLP: DB-9 female

DSCLP: DB-25 female to cable with 2 DB-9 female

QSCLP: HD-44 female to cable with 4 DB-9 female

Certifications: CE, FCC Class B, RoHS and WEEE compliant

Ordering Information:

SSCLP-200/300: One port RS-422/485 board

DSCLP-200/300: Two port RS-422/485 board with cable

QSCLP-200/300: Four port RS-422/485 board with cable



DSCLP-100 only
Microsoft, Windows, and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.



Diamond Point International (Europe) Ltd

Suite 13, Ashford House, Beaufort Court

Sir Thomas Longley Road, Rochester, Kent, ME2 4FA, UK

Phone 01634 300900 - Fax 01634 722398 - Email sales@dpie.com - Web www.dpie.com



www.dpie.com